


Cleaning and maintenance of the **Infinity** surfaces



Countertop cleaning

For ordinary cleaning, a cloth dampened with water and neutral soap is perfectly adequate.

For more persistent or burned-on stains, we recommend moistening the dirt with hot water (to soften any residues) and then rinsing or removing with a clean cloth. It is also preferable to use a sponge with soft fibres of the type normally used for cleaning glass ceramic and glassware in general. Particularly abrasive sponges or steel wool must be avoided at all costs.

Infinity recommends against treating the slabs with caustic soda. We also recommend to do not have long application timing both with acid and alkaline products.

If bleach is used, we suggest an application of 10-15 minutes and rinse with plenty of water and never leave the product to remain in contact with the surface of the Infinity surfaces more than the timing specified before.

For the correct maintenance of the slabs, Infinity recommends that you abide by the following precautions:

- **Always use pan stands, coasters and napkins;**
- **It is wise not to cut foods directly on the countertop but to use chopping boards for this purpose;**
- **Never drag household appliances, knives and utensils in general across the countertop, as this may leave steel stains that are difficult to remove;**
- **Never use ceramic knives directly on the countertop.**



HEAT RESISTANCE

Infinity surface complies to the performances required by the EN ISO 10545-1 standard in terms of resistance to thermal shocks.

In particular, Infinity surface tolerates brief exposures to quite hot temperature, however a direct contact with a very hot objects may cause thermal shock and damages. We therefore do not recommend placing hot items directly from hotplate or out of the oven onto the Infinity surface.

We always recommend the use of a trivet to place hot items on.



Floor cleaning

After laying the material it is essential to clean them thoroughly. If residues of grouting are not removed properly or quickly, this may result in stains that are difficult to remove and may create a film of concrete on the floor that traps all kinds of dirt.

To efficiently remove any residues of cement-based grout, it is essential to wash the floor with a solution of water and buffered acid, following the percentages of water/acid indicated on the packaging of the product used.

Allow the detergent to work for a few minutes without letting it dry out, then wipe over the floor with colourless cloths (remove any residues with a stiff brush).

Finally rinse with plenty of water and repeat the operation as necessary.

ORDINARY FLOOR CLEANING

Infinity recommends against the use of oily soaps and waxes, and recommends instead neutral detergents such as ammonia or bleach, that have been suitably diluted in water.

After washing, the floor should only be dried if it has

a polished finish (to avoid any visible stains from appearing).

We always recommending testing any detergent before use, always following the instructions and the precautions indicated by the manufacturer.

EXTRAORDINARY FLOOR CLEANING

In the case of residues and stains that are particularly stubborn and difficult to remove, Infinity suggests cleaning the surface first with warm water and neutral detergents.

For persistent stains, then use more intense cleaning methods using specific products (depending on the type of stain to be treated):

- **Non-abrasive detergents with a neutral pH;**
- **Slightly abrasive detergents;**
- **Acid or alkaline detergents;**
- **Solvent-based detergents.**

We recommend always following the instructions and precautions indicated by the manufacturer.



Cleaning products

TYPES OF DETERGENT Where sale is permitted	SOLVENTS (bleach, turpentine, acetone, trichloroethylene, nitro thinner)		ACIDS (muriatic acid, hydrochloric acid, phosphoric acid)		ALKALINE-BASED DETERGENTS - ALKALI (professional alkaline detergents)	
SURFACE	Matt - Satin	Polished	Matt - Satin	Polished	Matt - Satin	Polished
TYPES OF STAIN						
Beer				■	■	
Coffee		■				
Lime scale			■	■		
Tar	■	■				
Concrete			■	■		
Candle wax	■	■				
Coca Cola		■				
Glue	■	■				
Chewing gum	■	■			■	
Rubber marks from tyres or shoes	■	■				
Grease, Oil					■	■
Ink	■	■				
Nicotine	■	■				
Felt-tip pen	■	■				
Tomato		■				
Resins	■	■				
Rust			■	■		
Nail varnish	■	■				
Cigarette burns			■	■		
Tea		■				
Wall paint	■	■	■	■		
Red wine		■				

i In view of the technical characteristics of the material, we recommend first trying to remove any stain using hot water, and to resort to specific products only if the result is not satisfactory.
For information and advice, please contact Infinity directly.

Distributed by:



international slab sales

JOHANNESBURG (HEAD OFFICE)

69 Serenade Road, Elandsfontein
Johannesburg, 1401
P O BOX 14336, Witfield, 1467
Tel +27 11 822 1350
Fax +27 11 822 1701
headoffice@interslab.co.za

JOHANNESBURG (BRANCH)

69 Serenade Road, Elandsfontein
Johannesburg, 1401
Tel +27 11 966 7999
Fax +27 10 020 1386
issjhb@interslab.co.za

CAPE TOWN (WESTERN CAPE)

10 Gold Street, Northgate Estate
Brooklyn, Cape Town, 7405
Tel +27 21 511 2353
Fax + 27 21 511 2505
issctn@interslab.co.za

DURBAN (KWA-ZULU NATAL)

133 Rockdale Road
Springfield Park, Durban, 4051
Tel +27 31 577 2828
Fax +27 31 577 0341
issdbn@interslab.co.za

PRETORIA (GAUTENG)

176 Vonkprop Street
Samcor Park Ext 1, Pretoria. 0184
Tel +27 12 803 5671
Fax +27 12 803 7696
isspta@interslab.co.za

PORT ELIZABETH (EASTERN CAPE)

4 Leadwood Crescent (off upper Willow Road)
Fairview, Port Elizabeth, 6070
Tel + 27 41 367 5571
Fax + 27 41 367 4829
isspe@interslab.co.za

NELSPRUIT (MPUMALANGA)

19 Bulpin Street,
Nelspruit, 1201
Tel + 27 13 752 8325
Fax + 27 13 752 5386
issnls@interslab.co.za

GEORGE (GARDEN ROUTE)

5 Commercial Close,
George, 6529
Tel + 27 44 871 1099
Fax +27 44 871 2625
issgrg@interslab.co.za



INFINITY™
The engineered surface.